



PRIME TX ATX 3.1



SPECIAL FEATURES

- ❖ ATX 3.1 and PCIe 5.1 Compatible
- ❖ Ultra-high Efficiency, 80 PLUS® Titanium Certified
- ❖ Cybenetics ETA Titanium and Lambda A Certified
- ❖ Fully Modular
- ❖ Native 12V-2x6 cable
- ❖ Top-Quality 135 mm Fluid Dynamic Bearing Fan
- ❖ Digital Hybrid Fan Control
- ❖ Micro Tolerance Load Regulation (MTLR) [0.5 %]
- ❖ Super Low Ripple Noise [under 20 mV] *
- ❖ Cable-free Connection Design
- ❖ Gold Plated High Current Terminal (MB, CPU and PCIe)
- ❖ Multi-GPU Technology Support

* under 25 mV for 1000 W

POWER DISTRIBUTION

Model	+3.3 V	+5 V	+12 V	-12 V	+5 Vsb	Total Power
PRIME TX-1600	25 A	25 A	133.3 A	0.5 A	3 A	1600 W
	125 W		1600 W	6.0 W	15 W	
PRIME TX-1300	25 A	25 A	108 A	0.3 A	3 A	1300 W
	125 W		1296 W	3.6 W	15 W	



CONNECTOR QUANTITY

Model	Cable	Main Power (24P / 20P)	EPS 12 V / ATX 12 V (8P / 4P)	12V-2x6 (12+4 Pins)	PCI-E (8P / 6P)	SATA	SATA 3.3	Peripheral (4P)
		610 mm	700 mm	700 mm	750 mm	950 mm	550 mm	690 mm
PRIME TX-1600	1	3	2	6	16	2	3	
PRIME TX-1300	1	3	1	6	16	2	3	



For more information on Cybenetics certifications please visit: www.cybenetics.com.



Compliance:

Protection Features: OPP / OVP / UVP / SCP / OCP / OTP

Dimensions: 210 mm (L) x 150 mm (W) x 86 mm (H)

Specifications may change without prior notice



Headquarters sales@seasonic.com
 USA ssa.sales@seasonic.com
 Europe sse.sales@seasonic.com