



Highlights

- Available in capacities ranging from 2TB to 26TB¹
- For RAID-optimized NAS systems with unlimited # of bays
- Rated for 550TB/year workloads and up to 2.5M hours MTBF

Ideal for:

- Multimedia Creative Pros
- Medium to Large Businesses
- Commercial and Enterprise NAS systems



WD Red[®] Pro NAS Hard Drive

Enterprise-class hard drives engineered to deliver high performance and reliability to commercial and enterprise NAS environments.

WD Red[®] Pro drives are engineered to handle high-intensity workloads in 24x7 multi-user commercial and enterprise NAS environments. WD Red Pro drives deliver the performance, scalability and dependability businesses require to store, share and collaborate on large amounts of data in multi-bay RAID-optimized NAS systems.

Optimized for NAS with NASware™

Western Digital's exclusive NASware™ technology **fine tunes drive parameters** to match NAS system workloads, which helps increase performance and reliability.

Designed for Continuous Operation

WD Red Pro hard drives are designed to handle the rigorous demands of high-intensity **24x7 multi-user NAS environments** and increase system durability.

Tested for Dependable Compatibility

Western Digital partners with a wide range of NAS system vendors for **extensive testing** to ensure compatibility with most NAS enclosures.

Protected against Excessive Vibration

WD Red Pro drives include **Rotation Vibration (RV)** sensors that anticipate and proactively counteract disturbances caused by increased vibration. By dispersing excess vibration across the drive chassis, turbulence is minimized, performance is maintained and drives are protected.

Built to Absorb Shock

WD Red Pro hard drives include a **multi-axis shock sensor** to detect subtle shock events and automatically compensate with **dynamic fly height technology** to further protect the drives in NAS enclosures.

Engineered with Industry-Leading Technology

WD Red Pro 22TB¹, 24TB¹ and 26TB¹ hard drives feature Western Digital's proprietary OptiNAND™ technology which leverages **integrated iNAND embedded flash** to perform key housekeeping functions, freeing up more capacity and improving the overall drive performance.

Backed by World-Class Support and Warranty

As an industry-leading hard drive manufacturer, Western Digital stands behind their NAS storage solutions with the assurance of a **5-year limited warranty**⁷ and world-class support services for hassle free data storage.

WD Red[®] Pro NAS Hard Drive

Specifications

Model Number	WD260KFGX	WD241KFGX	WD240KFGX	WD221KFGX	WD202KFGX	WD201KFGX	WD181KFGX
Formatted capacity ¹	26TB	24TB	24TB	22TB	20TB	20TB	18TB
Recording Technology	CMR	CMR	CMR	CMR	CMR	CMR	CMR
Interface	SATA	SATA	SATA	SATA	SATA	SATA	SATA
Form factor	3.5-inch	3.5-inch	3.5-inch	3.5-inch	3.5-inch	3.5-inch	3.5-inch
Drive Technology	Helium	Helium	Helium	Helium	Helium	Helium	Helium
RV Sensors	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Advanced Format (AF)	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Native Command queuing	Yes	Yes	Yes	Yes	Yes	Yes	Yes
OptiNAND™ technology	Yes	Yes	Yes	Yes	Yes	Yes	No
RoHS compliant ²	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Performance							
Interface transfer rate (max) Buffer to host	6Gb/s	6Gb/s	6Gb/s	6Gb/s	6Gb/s	6Gb/s	6Gb/s
Internal transfer rate (max) ³	287MB/s	287MB/s	287MB/s	265MB/s	285MB/s	268MB/s	272MB/s
Cache (MB) ¹	512	512	512	512	512	512	512
RPM	7200	7200	7200	7200	7200	7200	7200
Reliability/Data Integrity							
Load/unload cycles ⁴	6,00,000	6,00,000	6,00,000	6,00,000	6,00,000	6,00,000	6,00,000
Non-recoverable read errors per bits read	<1 in 10 ¹⁵	<1 in 10 ¹⁵	<1 in 10 ¹⁵	<1 in 10 ¹⁵	<1 in 10 ¹⁵	<1 in 10 ¹⁵	<1 in 10 ¹⁵
MTBF ⁵ (hours)	25,00,000	25,00,000	25,00,000	25,00,000	25,00,000	25,00,000	25,00,000
Workload rate ⁶ (TB/year)	550	550	550	550	550	550	550
Limited warranty ⁷ (years)	5	5	5	5	5	5	5
Power Management⁸							
12VDC ±10% (A, peak)	1.7	1.7	1.7	1.7	1.8	1.8	1.8
Average Power (W)							
Read/Write	6.0	6.0	6.4	6.8	6.1	6.9	6.1
Idle	3.6	3.6	3.9	3.4	3.6	3.8	3.6
Standby/Sleep	1.1	1.1	1.2	1.2	0.9	1.6	0.9
Environmental Specifications							
Temperature (°C)							
Operating	5°C to 65°C	5°C to 65°C	0°C to 65°C	0°C to 65°C	0°C to 65°C	0°C to 65°C	0°C to 65°C
Non-operating	-40°C to 70°C	-40°C to 70°C	-40°C to 70°C	-40°C to 70°C	-40°C to 70°C	-40°C to 70°C	-40°C to 70°C
Shock							
Operating (2 ms, read/write)	40	40	40	40	50	30	50
Operating (2 ms, read)	40	40	40	40	50	50	50
Non-operating (2 ms)	200	200	200	200	250	250	250
Acoustics (dBA)							
Idle dBA	25	25	20	20	20	20	20
Seek (average) dBA	32	32	32	32	32	32	36
Country of Origin	TH	TH	TH	TH	TH	TH	TH
Physical Dimensions							
Height (max) (in / mm)	1.028 / 26.1	1.028 / 26.1	1.028 / 26.1	1.028 / 26.1	1.028 / 26.1	1.028 / 26.1	1.028 / 26.1
Length (max) (in / mm)	5.787 / 147	5.787 / 147	5.787 / 147	5.787 / 147	5.787 / 147	5.787 / 147	5.787 / 147
Width (± .01 in.) (in / mm)	4 / 101.6	4 / 101.6	4 / 101.6	4 / 101.6	4 / 101.6	4 / 101.6	4 / 101.6
Weight (± 3%) (lb / kg)	1.47 / 0.67	1.47 / 0.67	1.48 / 0.67	1.48 / 0.67	1.52 / 0.69	1.52 / 0.69	1.52 / 0.69

WD Red® Pro NAS Hard Drive

Specifications

Model Number	WD161KFGX	WD142KFGX	WD141KFGX	WD122KFBX	WD121KFBX	WD103KFBX	WD102KFBX
Formatted capacity ¹	16TB	14TB	14TB	12TB	12TB	10TB	10TB
Recording Technology	CMR	CMR	CMR	CMR	CMR	CMR	CMR
Interface	SATA	SATA	SATA	SATA	SATA	SATA	SATA
Form factor	3.5-inch	3.5-inch	3.5-inch	3.5-inch	3.5-inch	3.5-inch	3.5-inch
Drive Technology	Helium	Helium	Helium	Air	Air	Air	Air
RV Sensors	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Advanced Format (AF)	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Native Command queuing	Yes	Yes	Yes	Yes	Yes	Yes	Yes
OptiNAND™ technology	No	No	No	No	No	No	No
RoHS compliant ²	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Performance							
Interface transfer rate (max) Buffer to host	6Gb/s	6Gb/s	6Gb/s	6Gb/s	6Gb/s	6Gb/s	6Gb/s
Internal transfer rate (max) ³	259MB/s	265MB/s	255MB/s	267MB/s	240MB/s	267MB/s	265MB/s
Cache (MB) ¹	512	512	512	512	256	512	256
RPM	7200	7200	7200	7200	7200	7200	7200
Reliability/Data Integrity							
Load/unload cycles ⁴	6,00,000	6,00,000	6,00,000	6,00,000	6,00,000	6,00,000	6,00,000
Non-recoverable read errors per bits read	<1 in 10 ¹⁵	<1 in 10 ¹⁵	<1 in 10 ¹⁴	<1 in 10 ¹⁵	<1 in 10 ¹⁵	<1 in 10 ¹⁵	<1 in 10 ¹⁵
MTBF ⁵ (hours)	25,00,000	25,00,000	25,00,000	20,00,000	20,00,000	20,00,000	20,00,000
Workload rate ⁶ (TB/year)	550	550	550	550	550	550	550
Limited warranty ⁷ (years)	5	5	5	5	5	5	5
Power Management⁸							
12VDC ±10% (A, peak)	1.8	1.8	1.8	1.9	1.8	1.9	1.75
Average Power (W)							
Read/Write	6.1	6.4	6.2	8.8	6.0	8.8	8.4
Idle	3.6	3.6	3.0	6.1	2.8	6.1	4.6
Standby/Sleep	0.9	0.9	0.8	0.3	0.6	0.3	0.5
Environmental Specifications							
Temperature (°C)							
Operating	0°C to 65°C	0°C to 65°C	0°C to 65°C	0°C to 65°C	0°C to 65°C	0°C to 65°C	0°C to 65°C
Non-operating	-40°C to 70°C	-40°C to 70°C	-40°C to 70°C	-40°C to 70°C	-40°C to 70°C	-40°C to 70°C	-40°C to 70°C
Shock							
Operating (2 ms, read/write)	50	50	30	70	30	70	30
Operating (2 ms, read)	50	50	65	70	65	70	65
Non-operating (2 ms)	250	250	300	250	300	250	250
Acoustics (dBA)							
Idle dBA	20	20	20	34	20	34	34
Seek (average) dBA	36	36	36	39	36	39	38
Country of Origin	TH	TH	TH	TH	TH	TH	TH
Physical Dimensions							
Height (max) (in / mm)	1.028 / 26.1	1.028 / 26.1	1.028 / 26.1	1.028 / 26.1	1.028 / 26.1	1.028 / 26.1	1.028 / 26.1
Length (max) (in / mm)	5.787 / 147	5.787 / 147	5.787 / 147	5.787 / 147	5.787 / 147	5.787 / 147	5.787 / 147
Width (± .01 in.) (in / mm)	4 / 101.6	4 / 101.6	4 / 101.6	4 / 101.6	4 / 101.6	4 / 101.6	4 / 101.6
Weight (± 3%) (lb / kg)	1.52 / 0.69	1.52 / 0.69	1.52 / 0.69	1.65 / 0.75	1.46 / 0.66	1.65 / 0.75	1.65 / 0.75

WD Red® Pro NAS Hard Drive

Specifications

Model Number	WD8005FFBX	WD8003FFBX	WD6005FFBX	WD6003FFBX	WD4005FFBX	WD4003FFBX	WD2002FFSX
Formatted capacity ¹	8TB	8TB	6TB	6TB	4TB	4TB	2TB
Recording Technology	CMR	CMR	CMR	CMR	CMR	CMR	CMR
Interface	SATA	SATA	SATA	SATA	SATA	SATA	SATA
Form factor	3.5-inch	3.5-inch	3.5-inch	3.5-inch	3.5-inch	3.5-inch	3.5-inch
Drive Technology	Air	Air	Air	Air	Air	Air	Air
RV Sensors	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Advanced Format (AF)	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Native Command queuing	Yes	Yes	Yes	Yes	Yes	Yes	Yes
OptiNAND™ technology	No	No	No	No	No	No	No
RoHS compliant ²	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Performance							
Interface transfer rate (max) Buffer to host	6Gb/s	6Gb/s	6Gb/s	6Gb/s	6Gb/s	6Gb/s	6Gb/s
Internal transfer rate (max) ³	267MB/s	235MB/s	267MB/s	238MB/s	267MB/s	217MB/s	164MB/s
Cache (MB) ¹	256	256	256	256	256	256	64
RPM	7200	7200	7200	7200	7200	7200	7200
Reliability/Data Integrity							
Load/unload cycles ⁴	6,00,000	6,00,000	6,00,000	6,00,000	6,00,000	6,00,000	6,00,000
Non-recoverable read errors per bits read	<1 in 10 ¹⁵	<1 in 10 ¹⁵	<1 in 10 ¹⁵	<1 in 10 ¹⁵	<1 in 10 ¹⁵	<1 in 10 ¹⁵	<1 in 10 ¹⁵
MTBF ⁵ (hours)	20,00,000	20,00,000	20,00,000	20,00,000	20,00,000	20,00,000	20,00,000
Workload rate ⁶ (TB/year)	550	550	550	550	550	550	550
Limited warranty ⁷ (years)	5	5	5	5	5	5	5
Power Management⁸							
12VDC ±10% (A, peak)	2.04	2.08	2.00	1.79	2.00	1.79	1.9
Average Power (W)							
Read/Write	6.9	8.8	6.9	7.2	5.8	7.2	7.8
Idle	4.9	4.6	4.9	3.7	4.0	3.7	6.0
Standby/Sleep	0.3	0.7	0.3	0.4	0.3	0.4	1.4
Environmental Specifications							
Temperature (°C)							
Operating	0°C to 65°C	0°C to 65°C	0°C to 65°C	0°C to 65°C	0°C to 65°C	0°C to 65°C	0°C to 65°C
Non-operating	-40°C to 70°C	-40°C to 70°C	-40°C to 70°C	-40°C to 70°C	-40°C to 70°C	-40°C to 70°C	-40°C to 70°C
Shock							
Operating (2 ms, read/write)	70	30	70	30	70	30	30
Operating (2 ms, read)	70	65	70	65	70	65	65
Non-operating (2 ms)	300	300	300	300	300	300	300
Acoustics (dBA)							
Idle dBA	29	29	29	29	29	29	29
Seek (average) dBA	36	36	36	36	36	36	31
Country of Origin	TH	TH	TH	TH	TH	TH	TH
Physical Dimensions							
Height (max) (in / mm)	1.028 / 26.1	1.028 / 26.1	1.028 / 26.1	1.028 / 26.1	1.028 / 26.1	1.028 / 26.1	1.028 / 26.1
Length (max) (in / mm)	5.787 / 147	5.787 / 147	5.787 / 147	5.787 / 147	5.787 / 147	5.787 / 147	5.787 / 147
Width (± .01 in.) (in / mm)	4 / 101.6	4 / 101.6	4 / 101.6	4 / 101.6	4 / 101.6	4 / 101.6	4 / 101.6
Weight (± 3%) (lb / kg)	1.58 / 0.72	1.58 / 0.72	1.58 / 0.72	1.58 / 0.72	1.58 / 0.72	1.58 / 0.72	1.58 / 0.72

¹ 1MB = 1 million bytes, 1GB = 1 billion bytes, and 1TB = 1 trillion bytes. Actual user capacity may be less depending on operating environment.

² This drive is in compliance with the European Union Directive 2011/65/EU and Directive (EU) 2015/863 on the restriction of the use of certain hazardous substances (RoHS) in electrical and electronic equipment.

³ Up to stated speed. 1 MB/s = 1 million bytes per second. Based upon read speed, unless otherwise stated. Performance may vary depending upon host device, usage conditions, drive capacity and other factors.

⁴ Controlled unload at ambient condition.

⁵ Projected Values. When final, MTBF are based on a sample population and are estimated by statistical measurements and acceleration algorithms under typical operating conditions, workload of 220TB/year and drive temperature of 40C. Derating of MTBF will occur above these parameters, up to 550TB writes per year. MTBF do not predict an individual drive's reliability and do not constitute a warranty.

⁶ Annualized Workload Rate = TB transferred x (8760 / recorded power-on hours). The maximum rated workload is specified for operating at typical temperature of 40C. Workload Rate will vary depending on your hardware and software components and configurations.

⁷ See <http://support.wd.com/warranty> for regional specific warranty details.

⁸ Power measurements at room-ambient temperature.

