

RG-EW300 PRO 300Mbps Wireless Smart Router

DATASHEET



/ Highlights


- Stronger signal with 4 x 5dBi antenna and signal amplifiers
- Easy management, easy life
- Life-time free cloud management supported

/ Highlight Features



Stronger Signal than the Average

Equipped with signal amplifiers (FEM), four 5dBi omnidirectional antennas guarantee you efficient and stable connections.





/ Highlight Features

WISP & Repeater Mode Supported


Newly-added WISP & Repeater mode can amplify Wi-Fi signals to wider range. Enjoy whole-room WiFi coverage and lag free network.







Highlight Features



.

/ Specifications

Basic Basic		
Dimensions (W×D×H)	210 mm × 180 mm × 33 mm (8.27 in. ×7.09 in. × 1.3 in. antennas not included)	
Weight	0.2615 kg (packages not included)	
Wi-Fi Standards	Wi-Fi 4 (802.11n)	
мімо	2.4 GHz, 2×2, MIMO	
Max. Wi-Fi Speed	2.4 GHz: 300 Mbps	
Channel Width	2.4 GHz: Auto/20/40 MHz	
Antennas	4	
Antennas Type	External Omnidirectional	
Antennas Gain	2.4 GHz: 5 dBi	
WAN Port	1×10/100Base-T	
WAN Port	3×10/100Base-T	
Recommended Users	8	
Max. Users	16	
Power Supply	DC 12V/1.0A	
Power Consumption	< 12 W	
Operation Frequency Bands	802.11b/g/n: 2.412 GHz to 2.472 GHz country-specific restrictions apply	
Transmit Power	≤20dBm (2.4GHz) Country-specific restrictions apply	
Receive Sensitivity	2.4 GHz:20MHz 802.11b: -94 dBm(1 Mbps), -81dBm(11Mbps) 802.11g: -86 dBm(6 Mbps), -70 dBm(54 Mbps) 802.11n (HT20): -87dBm (MCS0), -69 dBm (MCS7) 802.11n (HT20): -84 dBm (MCS0), -66 dBm (MCS7)	
Operating Temperature	-10 °C to 40 °C (14 °F to 104 °F)	
Operating Humidity	5% to 95% Noncondensing	

Certifications	CE, RoHS	
Wireless		
Maximum Number of SSIDs	8	
Hide SSID	Support	
Guest Wi-Fi	Support	
WPA/WPA2	Support	
Blocklist	Support	
Wi-Fi Optimization	-	
Transmission Power Adjustment	Support	
Hardware		
Flash	16 MB	
Memory	64 MB	
Color	Black	
System LED Indicator	Support	
Power Button	-	
Reset Button	Support	
Power Consumption	<12W	
	WAN	
Static IP	Support	
DHCP	Support	
PPPoE	Support	
VLAN Tag	Support	
VLAN Tagging	Support	
LAN		
DHCP Server	Support	
Client List	Support	

	reatures	
TDN40 Su	Features	
rpn40		
34	upport	
Preset Su	upport	
Pv6 Su	upport	
DDNS Su	upport	
PTV Su	upport	
Alarm Su	upport	
Diagnosis Su	upport	
JPnP Su	upport	
ARP Binding Su	upport	
Port Mapping Su	upport	
DMZ Host Su	upport	
Rate Limitation of Terminals Su	upport	
Hardware NAT Su	upport	
MAC Address Cloning Su	upport	
Cloud Management Su	upport	
Repeater Mode Su	upport	
WISP Mode Su	upport	
AP Mode Su	upport	
Security		
Parental Control Sc	chedule	
Protect TCP Flood Attacks Su	upport	
System		
Default IP Address	2.168.110.1	

URL Access	Support	
Local Upgrade	Support	
Online Upgrade	Support	
APP Upgrade	Support	
Syslog	Support	
Backup	Support	
Factory Reset	Support	
Package Contents		
	Package Contents	
Package Information	Package Contents RG-EW300 PR0	
Package Information	RG-EW300 PRO	
Package Information Wireless Router	RG-EW300 PRO 1	
Package Information Wireless Router Power Adapter	RG-EW300 PRO 1 1	

Package Contents

Wireless Router	1
Power Adapter	1
Quick Start Guide	1
Warranty Card	1
Cat5E UTP Cable	1





Copyright ©2000-2024 Ruijie Networks Co., Ltd. All rights reserved.

No part of this document may be reproduced or transmitted in any form or any means without prior written consent of Ruijie Networks Co., Ltd.

Notice

This content is applicable only to regions outside the China mainland. Ruijie Networks Co., Ltd. reserves the right to interpret this content.

The information contained herein is subject to change without notice. Nothing herein should be construed as constituting an additional warranty. Ruijie Networks Co., Ltd. shall not be liable for technical or editorial errors or omissions contained herein.



Ruijie Networks Co., Ltd.
Website: https://reyee.ruijie.com/en-global