

Model

FS1024

24-Port 10/100 Mbps
Unmanaged Ethernet Switch



Datasheet



Highlights

A 24-FE switch with VLAN/Extend functions and a fanless cooling system.

- RTL8324E-CG + RTL8208D
- 24× Fast Ethernet Ports
- Fanless Cooling
- Default/VLAN/Extend DIP Switch
- Extend for 250 Meters Transmission
- VLAN for Clients Isolation

Specifications

Protocols	802.3 Protocols	802.3x Flow Control
		802.3i 10BASE-T
		802.3u 100BASE-T
CPU	Chipset	RTL8324E-CG + RTL8208D
Interfaces	Physical Buttons	VLAN/Default/Extend DIP Switch
	10/100 Mbps RJ45 Ports	24
	VLAN Mode Ports	#1~#22
	Extend Mode Ports	#1~#22
	LED	Power
		Link/ACT of Each Ethernet Ports
	Power Input	AC Inlet

Performance	Copper Speed and Distance	Cat. 3 or higher cable: 100 meters at 10 Mbps; Cat. 5 or higher cable: 100 meters at 100 Mbps, 250 meters at 10 Mbps
	Copper Speed and Distance Note	250-meter transmission is only available on the Extend Mode ports.
	MAC Address Table	8K
	Max Switching Capacity	4.8 Gbps
	Max Forwarding Rate	3.571 Mpps
	Jumbo Frame	2 KB
	Packet Buffer	2 Mbit
Power	Software Power Saving	Default
	Power Methods	AC
	AC	90~260V 50/60Hz
Reliability	Grounding Methods	Three-Prong Plug
		Grounding Point
	Lightning/Surge Protection	RJ45: 4KV
		AC: CM 4KV/DM 2KV
	ESD Contact Protection	8KV
	ESD Air Protection	6KV
	Environment	Operating Temperature: 0 °C ~ 40 °C (32 °F ~ 104 °F)
		storage Temperature: -40 °C ~ 70 °C (-40 °F ~ 158 °F)
		Operating Humidity: 10% ~ 90% non-condensing
		Storage Humidity: 5% ~ 90% non-condensing



Specifications

Mechanical	Installation	Desktop
		Rack-Mounting
	Dimension	270×182×44 mm
		10.63×7.17×1.73 inches

Package Content

- FS1024
- Power Cord
- Installation Guide
- Mounting Kit