Ruíjie | Reyce

RG-EW300R 300Mbps Wi-Fi Extender

DATASHEET



Highlights

- Plug and play, easy and strong
- Two built-in signal amplifiers boost 1.5X signal strength
- Three-bar signal indicator guides you to find the best spot
- Flexible placement, one-click connection
- Take control of your home network at your fingertips





More Powerful than You Expect

Two built-in signal amplifiers boost 2X signal strength





| Ruíjie I sReyce | Three-bar Signal Indicator Guides You to Find the Best Spot |
|---|--|
| strong signal modest signal weak signal | EW300R clearly shows you the signal strength and guides you the best spot to position the repeater, while others only give you the "Yes or No" answer. |



Flexible Placement, One-click Connection

Press the WPS button on existing router and on EW300R within 2 minutes to easily connect to the network



More Wireless Mode Options, Meet All Your Needs

AP Mode for Work Repeater mode for entertainment More stable and reliable More flexible and chill









| | Basic |
|------------------------------|---|
| Dimensions (W×D×H) | 92 mm x 70 mm x 38 mm (3.62 in. × 2.76 in. × 1.50 in. antennas not included) |
| Weight | 0.14 kg (packages not included) |
| Wi-Fi Standards | Wi-Fi 4 (802.11n) |
| MIMO | 2.4 GHz, 2×2, MIMO |
| Max. Wi-Fi Speed | 2.4 GHz: 300 Mbps |
| Channel Width | 2.4 GHz: Auto/20/40 MHz |
| Antennas | 2 |
| Antennas Type | External Omnidirectional |
| Antenna Gain | 2.4 GHz: 4 dBi |
| Port | 1×10/100 Base-T WAN/LAN |
| Recommended Users | 8 |
| Max. Users | 16 |
| Power Supply | 100-240V~50/60Hz 0.5A |
| Power Consumption | ≤12W |
| Operation Frequency Bands | 802.11b/g/n: 2.412 GHz to 2.472 GHz country-specific restrictions apply |
| Transmit Power | <20 dBm (2.4 GHz) country-specific restrictions apply |
| Operating Temperature | -10 °C to +45 °C (14 °F to 113 °F) |
| Operating Humidity | 5% to 95% Noncondensing |
| Certifications | CE,RoHS |
| OFDMA | - |
| MU-MIMO | - |
| | |



| | Wireless |
|----------------------------------|--------------|
| BSS Coloring | - |
| Maximum Number of SSIDs | 3 |
| SSID Hiding | \checkmark |
| Band Steering | - |
| Guest Wi-Fi | \checkmark |
| WPA/WPA2 | \checkmark |
| WPA3 | - |
| Roaming | - |
| Blacklist | \checkmark |
| Reyee Mesh | - |
| Mesh Pairing by Hardware | |
| Mesh Pairing by Mesh Button | - |
| Mesh Pairing by Eweb | - |
| Recommended Hop Count | - |
| Wi-Fi Optimization | - |
| QoS (WMM) | - |
| WPS | \checkmark |
| Transmission Power Adjustment | \checkmark |
| | Hardware |
| CPU | MT7628DAN |
| Flash | 16 MB |
| RAM/SDRAM | 64 MB |
| Color | White |

Specifications

| Hardware | |
|--------------------------|--------------|
| System LED Indicator | \checkmark |
| Reyee Mesh LED Indicator | - |
| Reyee Mesh Button | - |
| Power Button | - |
| Reset Button | \checkmark |
| DC Connector Dimensions | - |

| WAN | |
|--------------------------------------|--------------|
| Static IP | \checkmark |
| DHCP | \checkmark |
| РРРоЕ | \checkmark |
| Learning PPPoE Account & Password | - |
| VLAN Tagging | \checkmark |
| | LAN |
| DHCP Server | \checkmark |
| Client List | \checkmark |
| Static IP Assignment | \checkmark |
| Port-Based Flow Control | - |

| | Features |
|-------|--------------|
| TR069 | \checkmark |
| IPv6 | \checkmark |
| DDNS | - |
| IPTV | - |
| Alarm | - |
| | |

Diagnosis



| | Features |
|---------------------------------|---|
| UPnP | - |
| ARP Binding | - |
| Port Mapping | - |
| DMZ Host | - |
| Rate Limitation of Terminals | - |
| Hardware Acceleration | - |
| MAC Address Cloning | \checkmark |
| Cloud Management | \checkmark |
| Repeater Mode | \checkmark |
| WISP Mode | \checkmark |
| | Security |
| PPTP VPN Server | - |
| PPTP VPN Client | - |
| L2TP VPN Client | - |
| Parental Control | - |
| Protect TCP Flood Attacks | \checkmark |
| Protect ICMP Attacks | - |
| Protect UDP Flood Attacks | - |
| | System |
| Default Access/Password | 10.44.77.254 No Password Required by Default |
| URL Access | - |
| Local Upgrade | \checkmark |
| Online Upgrade | \checkmark |



| System | |
|---------------|---|
| APP Upgrade | \checkmark |
| Syslog | - |
| Backup | - |
| Factory Reset | \checkmark |
| Language | Chinese English Vietnamese Indonesian Thai Arabic Traditional Chinese Spanish Russian |

Package Contents

| Device | RG-EW300R |
|-------------------|-----------|
| Wireless Extender | 1 |
| User Manual | 1 |
| Warranty card | 1 |

Rujje Rcycc

Redefine your easy network

Copyright ©2000-2024 Ruijie Networks Co., Ltd. All rights reserved. No part of this document may be reproduced or transmitted in any form or any means without prior written consent of Ruijie Networks Co., Ltd.

Notice

This content is applicable only to regions outside the China mainland. Ruijie Networks Co., Ltd. reserves the right to interpret this content.

The information contained herein is subject to change without notice. Nothing herein should be construed as constituting an additional warranty. Ruijie Networks Co., Ltd. shall not be liable for technical or editorial errors or omissions contained herein.



Ruijie Networks Co., Ltd. Website: https://reyee.ruijie.com/en-global